

DSC FORGED STEEL THERMODYNAMIC STEAM TRAPS








No.D80 \ D80F

MOP 46K x 430℃

- DSC D80 FOGED STEEL THERMODYNAMIC STEAM TRAPS WITH INSULATION CAP TO PROTECT STEAM CONSUMPTION DURING COLD AND RAINY CONDITIONS.
- ALL INTERNAL PARTS CAN BE REPLACED, NO NEED TO REMOVE TRAPS FROM PIPE LINE IF TRAP FAILS.
- DISC AND SEAT ARE LAPPED TO MEET LIGHT BAND FLATNESS, SEAT AND DISC ARE TIGHTLY SEALED DURING OPERATION.
- THIS MODEL CAN USE FOR SUPER HEAT STEAM SERVICE.
- SCREWED OR FLANGE CONNECTION AVAILABLE.





| TRAP NO. | CONN.SE.* | A | В | С | MOP | WT |
|----------|-----------|----|----|----|-----|-----|
| D80 | 15.20 | 85 | 51 | 63 | 46 | 1.1 |

^{*}NPT. BSPT. SW. AVAILABLE



| TRAP NO. | CONN.FE.* | A | В | С | MOP | WT |
|----------|-----------|-----|----|----|-----|-----|
| D80F | 15 | 150 | 51 | 63 | 46 | 3.5 |
| | 20 | 150 | 51 | 63 | 46 | 3.5 |

^{*} FLANGE SPEC CONSUAT FACTORY.

CONSTRUCTION OF MATERIALS

| INSULATION CAP | S.S 304 | | | |
|----------------|----------------------------|--|--|--|
| BODY | FORGED STEEL A105 | | | |
| DISC CAP | S.S 304 | | | |
| DISC | HARDENED S.S420 | | | |
| SEAT | HARDENED S.S420 | | | |
| GASKET | GRAPHITE | | | |
| SCREEN | PERFORATED S.S304 SHEET | | | |
| SCREEN PLUG | S.S 304 | | | |
| SCREEN GASKET | S.S 304 | | | |

CONDENSATE DISCHARGE CAPACITY IN KG/HR

